

ANY-Z™



USES:

* 2-way connections with angles up to 20° - 160° for AZ/NZ/EZ/Hoesch, PZ/PZC and most Cold Formed

* Also transitions any combination of the above mentioned sheet piles

steel grade
ASTM Grade
50/60,
ASTM A690


weight
~ 14.60 lb/ft
~ 21.7 kg/m

works with

AZ 12-770, AZ 13, AZ 13-770, AZ 14-770, AZ 17, AZ 17-700, AZ 18, AZ 18-700, AZ 19, AZ 19-700, AZ 24-700, AZ 25, AZ 26, AZ 26-700, AZ 28, AZ 28-700, AZ 36-700N, AZ 38-700N, AZ 40-700N, AZ 42-700N, AZ 44-700N, AZ 46, AZ 46-700N, AZ 48, AZ 50, EZ 18, EZ80, EZ88, EZ95, H 1807, H 2507, H 2607, H 2707, H 2807, H 3907, MSZ18 312, MSZ18 340, MSZ18 350, MSZ18 375, MSZ18 406, MSZ19 340, MSZ19 350, MSZ19 375, MSZ19 406, NZ 19, NZ 21, PZ 22, PZ 27, PZ 35, PZ 40, PZC 13, PZC 14, PZC

for AZ/NZ/EZ/ZZ

Connectors



Combined Sheet Pile



for PZ/PZC

Connectors

